

## **City of Dallas Prescriptive Path** Project Summary and Checklist - One or Two Family Dwelling Unit Addition

Summary										
Date of										
Application										
Compliance										
Path										
Project										
Identification										
Project										
Address										
Owner										
Identification										
Architect										
Identification										
Contractor										
Identification										
Third Party									Registration No.	
Provider										
		T			1	1		1		
Building Code	IRC	IBC Resident	ial Oc	ccupancy						
Type of Building	Cinada Family	Dumlass	Tau			IBC G	roup R Occ	cupancy: R-1 R-2 R-3		
	Single Family	Duplex	Townhouse*				circle one)			
Number of:	Stories:	Bedrooms:	Bat	hs:			•		·	
Garage	Attached			Detached			Carport		None	
Building Sq.	Lot Size:			Building Total Sq. Ft:			Area Under Roof:		Total Non roof Area:	
Footage										
IECC Climate	3A	•	•							
Zone										
Note:		·								

- Buildings shall be designed and constructed in accordance with the Energy provisions of Dallas Energy code. Compliance with IECC must be demonstrated separately by City of Dallas registered Third Party Energy Inspector
- All requirements mandatory
- Townhouse: As defined by the Dallas Residential Code; may not be multifamily building





**Prescriptive Provisions** Inspection Plan Review **Green Building Practice Field Notes Comments** Item Yes No N/A N/A Yes Submitted at plan review; verify at final 326.2.2.1.3.2.2 Water Efficiency inspection Must meet at least 2 of the Performance properties noted on drawings or specified; review submittal cut sheets; verify at following water reduction strategies: final inspection 1. The average flow rate for all Average flow rate is per fixture; refer to lavatory faucets must be less manufacturer's product literature. than or equal to 2.0 gallons per minute 2. The average flow rate for all shower head must be less than or equal to 2.0 gallons per minute 3. The average flow rate for all toilets must be: 3.1 Less than or equal to 1.3 gallons per flush, or 3.2 Dual flush complying with ASME A 112.19.14, or 3.3 Comply with US EPA Water Sense: certified and labeled All projects must meet with the minimum requirements of the 326.2.2.1.3.3 **Energy Efficiency** energy provisions of the 2015 IRC. Specified on drawings or specifications at Plan 326.2.2.1.3.4 Review; documented by construction **Heat Island Mitigation** submittals; verify at Final Inspection Proposed projects shall install any one of the following options: Option 1: An ENERGY STAR qualified roof on all roofs with a slope of 2:12 or greater. Option 2: A vegetated roof may Must be approved by BI at Plan Review be installed subject to approval by the Building Official.





Prescriptive Provisions										
Item	Green Building Practice	Plan Review		Inspection			Field Notes	Comments		
	Green Building Fractice	Yes	N/A	Yes	No	N/A	rieiu Notes	Comments		
	Option 3: Radiant barrier with conventional shingles.							Installation in accordance with manufacturer installation instructions required. Radiant barriers will be considered an alternative path to Energy Star and cool roofs, under the condition that the radiant barrier installation complies with the manufacturer's recommendations which include, but are not limited to: the shiny side of the sheet faces out; the sheet is factory perforated; it is not installed on the attic floor or where the shiny side may become covered with dust; and it is not sandwiched between materials such as insulation and roof shingles. if the radiant barrier is applied to roof sheathing, the radiant barrier must face down into the attic and may not be covered. Radiant barriers have no insulative or R value and are not used in place of insulation. Reflective paint is not considered a radiant barrier.		
	Option 4: Encapsulated foam insulation between the roof rafters (R-22 or greater)							Installation in accordance with manufacturer installation instructions required		
326.2.2.1.3.5	Indoor Air Quality							Show on drawings at Plan Review; verify at Final Inspection		
326.2.2.1.3.5.1	HVAC: All air-handling equipment and ductwork must be outside the fire-rated envelope of the garage.  Minimize Pollutants from the									
320.2.2.1.3.3.2	garage:									
326.2.2.1.3.5.2.1	Conditioned Spaces above a garage: 1. Penetrations sealed 2. Floor and ceiling joist bays sealed 3. Painted walls and ceilings of conditioned spaces.									





**Prescriptive Provisions** Plan Review Inspection **Green Building Practice** Field Notes Comments Item Yes N/A Yes No N/A 326.2.2.1.3.5.2.2 Conditioned Spaces next to a garage: 1. Penetration sealed 2. Doors weather stripped 3. Cracks at wall base sealed 326.2.2.1.3.5.3 Air Filters a. MERV 8 of greater b. Air handlers sized to maintain air pressure and air flow c. Airtight air filter housing End of Prescriptive

