

320 E Jefferson Blvd, Dallas TX 75203 (214) 948-4480

City of Dallas Prescriptive Path

Project Summary and Checklist - One or Two Family Dwelling Unit

					<u>Addition</u>		
				Summ	nary		
Date of							
Application							
Compliance							
Path							
Project							
Identification							
Project							
Address							
Owner							
Identification							
Architect							
Identification							
Contractor							
Identification							
Third Party							Registration No.
Provider							
Building Code	IRC	IBC Resident	ial Occupancy				
Type of Building	Single Family	Duplex	Townhouse*		IBC Group R Oco R-1 R-2	cupancy: (select one) R-3 R-4	
Number of:	Stories:	Bedrooms:	Baths:				
	otorico.	Douroomo.	Butho.				
Garage	Attached	_	Detache	ed	Carport		None
Building Sq.	Lot Size:		Building	g Total Sq. Ft:	Area U	nder Roof:	Total Non-roof Area:
Footage							
IECC Climate	2A						
Zone							
Note:							
Buildings	shall be designe	d and construc	ted in accorda	ance with the Energy	gy provisions of D	allas Energy code. Com	pliance with IECC must be
demonstra	ated separately b	y City of Dallas	s registered Th	ird Party Energy I	nspector		

• All requirements mandatory

• Townhouse: As defined by the Dallas Residential Code; may not be multifamily building

Together we are planning and building a better Dallas for all!



320 E Jefferson Blvd, Dallas TX 75203 (214) 948-4480

	-							
ltem	Green Building Practice	Plan Review Inspection			nspecti	on	Field Notes	Comments
item	Green Building Flactice	Yes	N/A	Yes	No	N/A	Tield Notes	comments
332.5.2	Water Efficiency							Submitted at plan review; verify at final inspection
332.5.2.2	Must meet at least 2 of the following water reduction strategies:1. The average flow rate for all lavatory faucets must be less than or equal to 2.0 gallons per minute2. The average flow rate for all shower head must be less than or equal to 2.0 gallons per minute3. The average flow rate for all toilets must be:3. The average flow rate for all toilets must be:3. Less than or equal to 1.3 gallons per flush, or							Performance properties noted on drawings or specified; review submittal cut sheets; verify at final inspection Average flow rate is per fixture; refer to manufacturer's product literature.
	<ul> <li>3.2 Dual flush complying with ASME A 112.19.14, or</li> <li>3.3 Comply with US EPA Water Sense; certified and labeled</li> </ul>							
332.5.3	Energy Efficiency		jects mu ons of Da				mum requirements of the	
332.5.4	Heat Island Mitigation					_	Specified on drawings or specifications at Plan Review; documented by construction submittals; verify at Final Inspection	
	Proposed projects shall install any one of the following options:							
	<b>Option 1:</b> An ENERGY STAR qualified roof on all roofs with a slope of 2:12 or greater.							
	<b>Option 2</b> : A vegetated roof may be installed subject to approval by the Building Official.			_				Must be approved by BI at Plan Review



320 E Jefferson Blvd, Dallas TX 75203 (214) 948-4480

Prescriptive Provisions								
ltem	Green Building Practice	Plan F	Review	Inspection			Field Notes	Comments
item			N/A	Yes	No	N/A	Tield Notes	Comments
	<b>Option 3</b> : Radiant barrier with conventional shingles.							Installation in accordance with manufacturer installation instructions required. Radiant barriers will be considered an alternative path to Energy Star and cool roofs, under the condition that the radiant barrier installation complies with the manufacturer's recommendations which include, but are not limited to: the shiny side of the sheet faces out; the sheet is factory perforated; it is not installed on the attic floor or where the shiny side may become covered with dust; and it is not sandwiched between materials such as insulation and roof shingles. if the radiant barrier is applied to roof sheathing, the radiant barrier must face down into the attic and may not be covered. Radiant barriers have no insulative or R value and are not used in place of insulation. Reflective paint is not considered a radiant barrier.
	<b>Option 4:</b> Encapsulated foam insulation between the roof rafters (R-22 or greater)							Installation in accordance with manufacturer installation instructions required
332.5.5							Show on drawings at Plan Review; verify at Final Inspection	
332.5.5.1	<b>HVAC</b> : All air-handling equipment and ductwork must be outside the fire-rated envelope of the garage.							
332.5.5.2	Minimize Pollutants from the garage:							
332.5.5.2.1	<ul> <li>Conditioned Spaces above a garage:</li> <li>1. Penetrations sealed</li> <li>2. Floor and ceiling joist bays sealed</li> <li>3. Painted walls and ceilings of conditioned spaces.</li> </ul>							

Together we are planning and building a better Dallas for all!





320 E Jefferson Blvd, Dallas TX 75203 (214) 948-4480

Prescriptive Provisions									
ltem	Green Duilding Presties	Plan Review		Inspection				Comments	
	Green Building Practice	Yes	N/A	Yes	es No N/A		Field Notes	Comments	
332.5.5.2.2	Conditioned Spaces next to a								
	garage:								
	1. Penetration sealed								
	<ol><li>Doors weather stripped</li></ol>								
	<ol><li>Cracks at wall base sealed</li></ol>								
332.5.5.2.3	Air Filters								
	a. MERV 8 of greater								
	b. Air handlers sized to maintain								
	air pressure and air flow								
	c. Airtight air filter housing								
	End of Prescriptive								

Together we are planning and building a better Dallas for all!

